

## GRAFFITI ENTRY IN PHONE DIALER

### Technical Field

5

[1001] This invention relates to telephony, and has particular relation to dialing a phone call.

### Background Art

10

[1002] Telephone networks originally required a human operator. A person wishing to place a call would tell the operator the name or number of person sought to be called, and the operator would put the call through. Later, pulse dialers -- driven by actual mechanical rotary dials -- replaced the operator. Rotating the dial would cause the dialer to produce a pulse string, and automatic machinery in the telephone network would interpret a sequence of pulse strings to put the call through.

[1003] After that, tone dialing became the norm. Depressing a key on a keypad would cause a dialer within the telephone to generate a tone, or (more precisely) a combination of tones. Electronic devices in the telephone network would interpret a sequence of tone combinations to put the call through. Despite the abolition of the mechanical rotary dial, the process continued to be called "dialing" a number.

[1004] Each pulse string in the old networks, representing a single dialed digit, may be viewed as a dial signal. Similarly, each tone combination in the more modern networks, similarly representing a single dialed digit, may be viewed as a dial signal.

A sequence of dial signals (including pauses when appropriate) forms the telephone number, in a network-useable format. The term "dial signal" is used herein distinctly from the term "dial tone", which indicates only that the network is ready to receive a sequence of dial signals.

### Brief Disclosure of the Invention

[1005] This invention extends dial signaling to the graphical user interface, or GUI. Numbers can be drawn on a touch-screen with a stylus, as in a conventional

Personal Digital Assistant, or PDA. The PALM brand of PDA, manufactured by 3Com Corporation and using the GRAFFITI brand of GUI, is suitable. Such numbers are converted to dial signals -- tone combinations or pulse strings -- and are used to place a phone call.

5 [1006] If desired, letters can be input to the touch-screen. Each letter is then converted to a number, which is then used to generate the appropriate dial signal. Alternatively, the appropriate dial signal may be generated directly from the letter.

[1007] Graphical input can also be used to signal a pause. This is of lesser importance when each character, whether number or letter, is used to immediately  
10 generate a dial signal. Often, however, the telephone user prefers to store the telephone number before dialing it, and to see the number (to ensure that it is correct) before pressing a "Talk" or "Dial" button. Indeed, most wireless telephone networks require such storage. In such situations, the user appreciates the visual feedback that a pause will be made when appropriate, and the telephone is constructed to actually  
15 make such a pause.

#### Brief Description of the Drawings

[1008] FIG. 1 is a block diagram of a telephone according to the present  
20 invention.

[1009] FIG. 2 is block diagram of graphic-to-character conversion.

[1010] FIG. 3 is a block diagram of intermediate conversion of alpha characters to numeric characters and then to dial signals.

[1011] FIG. 4 is a block diagram of direct conversion of alpha characters to dial  
25 signals.

[1012] FIG. 5 is a block diagram of the conversion of a pause character to a pause dial signal.

[1013] FIG. 6 is a block diagram of a method according to the present invention.

[1014] FIG. 7 is a block diagram of a method using a stylus and a touch-screen.

30 [1015] FIG. 8 is a block diagram of a method using an intermediate character conversion step.

[1016] FIG. 9 is a block diagram of a method using an intermediate alpha-to-numeric conversion step.

[1017] FIG. 10 is a block diagram of a method avoiding an intermediate alpha-to-numeric conversion step.

[1018] FIG. 11 is a block diagram of a pause-character-to-pause-dial-signal method.

5

### Detailed Description

[1019] FIG. 1 is a block diagram of a telephone according to the present invention. A telephone (100) includes a dialer (102) which includes a graphical user interface (GUI) (104). Graphical information (106) is applied to the GUI (104) and the dialer (102) converts it to a dial signal (108). The GUI (104) is preferably a touch-screen, operated by a stylus (110). The touch-screen (104) and stylus (110) are therefore considered to be part of the dialer (102).

[1020] FIG. 2 is block diagram of graphic-to-character conversion. In this embodiment of the invention, the dialer (102) of FIG. 1 is instead viewed as excluding the GUI (104). Thus, the graphical information (106) is applied to a graphic-to-character converter (202), which converts it to a character (204). It is this character (204), and not the graphical information (106) per se, which is applied to the dialer (206), which produces the dial signal (108).

[1021] FIG. 3 is a block diagram of intermediate conversion of alpha characters to numeric characters and then to dial signals. Some numeric character of the convention telephone keypad, such as the "1" and the "#", are not associated with any alpha characters. Other numeric characters are conventionally associated with alpha characters. The "3", for example, is associated with the "D", the "E", and the "F". Thus, if the graphic-to-character converter (202) generates an alpha character (302), the alpha character (302) is converted into a numeric character (304), which is in turn converted into a dial signal (306). If, on the other hand, the graphic-to-character converter (202) generates a numeric character (304), it is directly converted into the dial signal (306).

[1022] FIG. 4 is a block diagram of direct conversion of alpha characters to dial signals. All characters (402), whether alpha or numeric, are converted directly into a dial signal (404).

[1023] FIG. 5 is a block diagram of the conversion of a pause character (502) to a pause dial signal (504). FIG. 5 is included since a pause character is not really either alpha or numeric. A pause dial signal is a pause between other dial signals.

[1024] FIG. 6 is a block diagram of a method according to the present invention. Graphical information is entered (602), and then is converted (604) into a dial signal. It parallels FIG. 1, in that no intermediate conversion into a character is required. See FIG. 8.

[1025] FIG. 7 is a block diagram of a method using a stylus and a touch-screen. The entry of graphical information is accomplished by applying a stylus to a touch-screen (702). The follow-on conversion (702) is the same as the foregoing conversion (602).

[1026] FIG. 8 is a block diagram of a method using an intermediate character conversion step. It parallels FIG. 2. Graphical information is entered (802) and converted to a character (804). The character in turn is converted (806) to a dial signal.

[1027] FIG. 9 is a block diagram of a method using an intermediate alpha-to-numeric conversion step. Once graphical information has been converted (902) to a character, a determination is made (904) as to whether the character is numeric. If it is not numeric, it is converted (906) to a numeric character, which is then converted to a dial signal (908). If the character is numeric, it is converted to a dial signal (908) immediately. FIG. 9 parallels FIG. 3.

[1028] FIG. 10 is a block diagram of a method avoiding an intermediate alpha-to-numeric conversion step. Once the graphical information has been converted to a character (1002), it makes no difference (1004) whether the character is numeric. It is immediately converted to a dial signal (1006) in either case. FIG. 10 parallels FIG. 4.

[1029] FIG. 11 is a block diagram of a pause-character-to-pause-dial-signal method. Once the graphical information has been converted to a character (1102), a determination is made (1104) as to whether the character is a pause character. If it is, then it is converted (1106) to a pause dial signal; that is, a pause is inserted between other dial signals. If it is not, then it is converted (1108) to a regular dial signal.

Industrial Application

[1030] This invention is capable of exploitation in industry, and can be made and used, whenever is it desired to dial a telephone. The individual components of the apparatus and method shown herein, taken separate and apart from one another, may  
5 be entirely conventional, it being their combination that is claimed as the invention.

[1031] While various modes of apparatus and method have been described, the true spirit and scope of the invention are not limited thereto, but are limited only by the following claims and their equivalents, and such are claimed as the invention.

5  
10  
15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995